



MATERIAL SAFETY DATA SHEET



EFFECTIVE DATE: 11-1-92

REVISION NUMBER: 7

QUAKER STATE CORPORATION • P.O. Box 989, Oil City, Pennsylvania 16301.

I. IDENTIFICATION

PRODUCT NAME: Quaker State Deluxe Motor Oil (5W-30, 10W-40, Performance 20W-50)

CHEMICAL NAME: N/A

PRODUCT CODE: See "Notes" on page 4

FORMULA: Complex mixture of Petroleum Hydrocarbons plus Additives

CHEMICAL FAMILY: Petroleum Hydrocarbon

SYNONYMS: Multi-viscosity motor oil

DEPARTMENT OF HAZARD CLASSIFICATION: Not hazardous under DOT 172.101

TRANSPORTATION: SHIPPING NAME: Petroleum Lubricating Oil IDENTIFICATION #:
None

CAS #: Mixture

CAS NAME: Mixture

II. TYPICAL COMPOSITION

<u>MATERIAL</u>	<u>CAS #</u>	<u>% wt.</u>	<u>TLV (UNITS) (SOURCE)</u>	<u>HAZARD</u>
Mineral Oils [®]	Mixture	> 90	5 mg/M ³ TWA OSHA 1910.1000 (1989)	Respiratory Irritant
Additive Package*	Mixture	< 10	None	None
(includes Zinc Compounds)	Mixture	< 3	None	None

*Additive manufacturers consider their additive package to be proprietary information.

[®]We consider our blend of mineral oils to be proprietary information.

III. PHYSICAL DATA

<u>BOILING POINT</u> , 760 mm. Hg: N/D	<u>PHYSICAL STATE</u> : Liquid
<u>SPECIFIC GRAVITY</u> (H ₂ O = 1): .87	<u>VAPOR PRESSURE AT 20°C.</u> : N/D
<u>VAPOR DENSITY</u> (AIR = 1): N/D	<u>SOLUBILITY IN WATER, % BY WT.</u> : Nil
<u>PER CENT VOLATILES BY VOLUME</u> : Nil	<u>EVAPORATION RATE</u> (Butyl Acetate = 1): N/D
<u>APPEARANCE AND ODOR</u> : Dark liquid (thickness dependent on viscosity). Slight hydrocarbon odor.	

This information is, to the best of Quaker State Corporation's knowledge and belief, accurate and reliable. However, no representation, warranty, or guarantee is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

FOR FURTHER INFORMATION CALL: (814) 676-7676

IV. HEALTH HAZARD DATA

TLV AND SOURCE: Oil Mist, Mineral - TWA 5 mg/M³ TWA OSHA 1910-1000 (1989)

ACUTE EFFECTS OF OVEREXPOSURE

- SWALLOWING : Not expected to be acutely toxic by ingestion. May cause nausea and diarrhea.
- SKIN ABSORPTION: No data available.
- INHALATION : Not expected to be toxic by inhalation. However, breathing mineral oil mists at levels above the TLV may cause respiratory irritation and possible discomfort. The creation of an oil mist is unlikely when used as a motor oil.
- SKIN CONTACT : Material expected to cause no more than minor skin irritation following prolonged and/or repeated contact.
- EYE CONTACT : Expected to cause no more than minor transient eye irritation.

CHRONIC EFFECTS OF OVEREXPOSURE

None known. See Notes to Physician below.

EMERGENCY AND FIRST AID PROCEDURES

- SWALLOWING : If material is swallowed, do not induce vomiting and contact a physician.
- SKIN : Wash skin thoroughly with soap and water. Launder soiled clothing.
- INHALATION : Although inhalation of this material is unlikely, if respiratory discomfort or irritation occurs due to inhalation of oil mist, move person to fresh air. Contact a physician if discomfort or irritation continues.
- EYES : Flush with water for 15 minutes. If irritation continues, contact a physician.

NOTES TO PHYSICIAN

Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water. It is believed during use in internal combustion engines contamination of oil with low levels of cancer causing combustion products (poly nuclear aromatics) occurs.

V. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT |test method(s)|: 385° F, minimum (COC)

AUTO IGNITION TEMPERATURE: N/D

FLAMMABLE LIMITS IN AIR, % BY VOLUME: N/A

EXTINGUISHING MEDIA: CO₂, Dry Chemical, Foam, Water Fog. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

SPECIAL FIRE FIGHTING PROCEDURES: For small fires involving this material, no special procedure or precautions are necessary. For large storage fires involving this material and/or other lubricating products

do not enter any enclosed or confined space without full protective equipment including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Containers may burst when exposed to fire conditions.

VI. REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: High temperatures and open flame.

INCOMPATIBILITY (materials to avoid): Strong oxidizing agents.

HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS: Carbon dioxide, water vapor. May produce oxides of sulphur, nitrogen and phosphorus. Incomplete combustion can produce carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None known

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Clean up spills as soon as possible. Absorb large spills with commercially available absorbent materials, such as absorbent clay.

WASTE DISPOSAL METHOD:

Place contaminated material in disposable containers and bury in an approved landfill site per local, state and federal regulations.

VIII. PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (specify type): Not applicable for intended use. However, if unusual operating conditions create concentrations in excess of the TLV, an approved respirator is recommended.

VENTILATION: None needed for intended use. Special ventilation is necessary only if unusual operating conditions create concentrations in excess of the TLV.

PROTECTIVE GLOVES: Impervious protective gloves can minimize skin exposures where prolonged or repeated exposures can occur.

EYE PROTECTION: Although none normally necessary for intended use, safety glasses or a face shield can reduce the possibility of accidental eye contact.

OTHER PROTECTIVE EQUIPMENT: None normally necessary for intended use.

IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not store near high heat or open flames.

PRECAUTIONS DURING USE: Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material.

X. REGULATORY INFORMATION

OSHA: Not hazardous under 1910.1200 The Hazard Communication Standard.

SARA Title III: 1-3% Zinc Reportable under Sec. 313.

N.J. Right To Know: REPORTABLE CONTENTS: Motor Oil, Acrylic Copolymer 68171-46-0,
800967-5469 P*, 800967-5478 P*, 800967-5491 P*

*N.J. Trade Secret Registry No.

HAZARD IDENTIFICATION

NOTES

PRODUCT CODES

<u>Deluxe Motor Oils</u>			
<u>5W-30</u>	<u>10W-40</u>	<u>20W-50 Performance</u>	<u>Package</u>
36219	36319	36419	Bulk
36210	36310	36410	55 gal. drum
	36307		5 qt. pl. jug
436248	436348	436448	1 qt. pl. bottle